

INFRALAN® Duplex Jumper LC-LC 50/125μ, OM4

INFRALAN® Duplex Jumper LC-LC 50/125μ, OM4,

The INFRALAN® LC LWL duplex patch cables consist of defined components that are compliant with structured cabling according to ISO/IEC 11801 and EN50173-x. The connectors used comply with IEC 61754-20 and meet quality class B/2 according to IEC 61753-1.

The assembled patch cable has a halogen-free and flame-retardant sheath that complies with the standards IEC 60754-2, IEC 60332-1 and IEC 61034. The cable conforms to IEC 60793-2.

The INFRALAN® LC LWL patch cable is delivered packed in a polybag, in which a measuring protocol and clips for coding are enclosed. Furthermore, the fiber is marked with the INFRALAN® logo on the outer sheath and the connector.

Fibre type: Multimode 50/125

Category: OM4

Number of fibres: 2

Cable type: Duplex

Anti-buckling grommet: plugged on

Cable Ø: 2 mm

Coat color: erika violet

Flame retardant: according to EN 50265-2-1

Halogen-free: according to EN 50267-2-3

Connector type 1st side: LC Duplex

Colour 1: beige

Connector type 2. side: LC Duplex

Colour 2: beige

IL at 850nm < 0.2 dB

Working temperature: -20 to 70 °C

Storage temperature: -20 to 85 °C

Jacket material: LSZH

Length: 1,0m

Make: INFRALAN®

Part No.: IPL-DR-LCULCU-4-0100

INFRALAN® Duplex Jumper LC-LC 50/125μ, OM4

INFRALAN® Duplex Jumper LC-LC 50/125μ, OM4,
as described above, however:

Length: X,Xm

Make: INFRALAN®

Part No.: IPL-DR-LCULCU-4-XXXX

Structure Art. no:

IPL-DR-LCULCU-4-XXXX

-XXXX = Length = "0050" = 0,50m

Available in lengths:

0,50m / 1,00m / 2,00m / 3,00m / 5,00m / 10,00m