

INFRALAN® U-DQ(ZN)BH 144E 9/125µ G657A

INFRALAN® U-DQ(ZN)BH 96E 9/125µ G657A,

Universal Cable, Singlemode G657.A1, for fix application indoor and outdoor in plastic pipe systems, cable ducts and on platforms.

Material outer sheath LSZH coloured in black, metal free, longitudinal water blocking, Halogen free, central loose tube filled with gel, multifunctional Glasroving wrapping, two-layered, as stain relief element and non-metal rodent protection.

Harmonised Norm: EN 50575, halogen free according to EN 60754-1/2, low in smoke according to EN 61034-2, flame-retardant according to EN 60332-3-24 and EN 60332-1-2, EURO-fire protection class Eca.

Outer diameter:	13,1mm
Tensile, long term:	max. 5000N
Crush resistance:	max. 150N/cm
Bending radius:	200mm
Operating temperature, moved:	-20 bis 60°C
Operating temperature, dormant:	-40 bis 80°C
IL, max. 850nm:	0,36db/km
IL, max. 1300nm:	0,22db/km
Rayleigh Backscatter Coefficient 1310nm:	1, 4676
Rayleigh Backscatter Coefficient 1550nm:	1, 4682
Construct:	144E (12x12) Singlemode G.657.A1
VDE-Name:	U-DQ(ZN)BH 96E9/125
Fabricate:	INFRALAN®
Art.-No.:	544144.1L