


DATASHEET

Fiber Optic Inspection Microscope for 2,5mm and 1,25mm ferrules



Specification

- Eye-Safe video viewing, Ergonomic design
- Fast and easy focus due to one hand operation
- Large 3,5" display
- Operation by rechargeable battery pack
- Inspection of different kind of cable with mounted connectors possible
- Change inspection tips in seconds



Art.No.	CI-1100	File	CI-1100.indd		
Description	Fiber Optic Inspection Microscope for 2,5mm and 1,25mm ferrules				
Created	Date	Last revision	Date	Proved	Date
JB	13.09.2016	JB	13.09.2016	BF	20.10.2016

DATASHEET

Fiber Optic Inspection Microscope for 2,5mm and 1,25mm ferrules

Parameter	Camera
Field of view	~ 0,425mm x 0,320mm
Optical Resolution	0,5µm
Optical Magnification	400 times
Focus	Manual adjustment
Light Source	Blue LED
Dimensions	D= 35mm, L= 175mm (without cap)
Weight	200g
Parameter	Display
Display	3,5" LCD-TFT, 960 x 240 pixel, adjustable brightness and contrast
Dimensions	W= 105mm, H= 90mm, D= 45mm (folded)
Weight	255g (without battery)
Power Supply	9,6V battery pack or AC power supply
Battery Life	4 hours



Art.No.	CI-1100	File	CI-1100.indd		
Description	Fiber Optic Inspection Microscope for 2,5mm and 1,25mm ferrules				
Created	Date	Last revision	Date	Proved	Date
JB	13.09.2016	JB	13.09.2016	BF	20.10.2016